



MINIMUM 15mm DEPTH OF WETPOUR.

EXISTING SUB-BASE  
(CONCRETE OR TARMAC).

DRAINAGE HOLES MAY BE  
REQUIRED TO PROVIDE  
APPROPRIATE DRAINAGE.

RAMPED EDGE SHOULD BE AT A MINIMAL GRADIENT TO AVOID BECOMING A TRIP HAZARD.  
WETPOUR UP TO 50mm DEEP SHOULD HAVE A MAXIMUM GRADIENT OF 1:2  
WETPOUR GREATER THAN 50mm SHOULD HAVE A MAXIMUM GRADIENT OF 1:25

CHASE CUT INTO TARMAC TO PROVIDE  
EDGE FOR WETPOUR SURFACING.  
MINIMU DIMENSIONS SHOULD BE 60mm  
WIDE x 15mm DEEP.

DRAWING TITLE:

WETPOUR ONTO EXISTING  
SUB-BASE (TARMAC OR CONCRETE)

Drawn by: CS      Chk'd by: R.L (2.9.10)

© **HAND MADE PLACES LTD**

Kingsley House, Unit 14, Old Station Way,  
Bordon, Hants, GU35 9HH  
Tel 01420 474111 Fax 01420 474222  
e-mail: info@handmadeplaces.co.uk  
www: handmadeplaces.co.uk

